



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification ⁶ : H04M 1/72		A1	(11) International Publication Number: WO 97/09813
			(43) International Publication Date: 13 March 1997 (13.03.97)
(21) International Application Number: PCT/SE96/00992 (22) International Filing Date: 6 August 1996 (06.08.96) (30) Priority Data: 08/524,867 7 September 1995 (07.09.95) US (71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE). (72) Inventor: NGUYEN, Nam, D.; 2460 Murville, Quebec J4Y-1M9 (CA). (74) Agents: BOHLIN, Björn et al.; Telefonaktiebolaget LM Ericsson, Patent and Trademark Dept., S-126 25 Stockholm (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: PERSONAL COMMUNICATIONS TERMINAL

(57) Abstract

A personal communications terminal (PCT) (10) in a case having a first half hingedly connected to a second half. The PCT operates in an open and a closed position and comprises a mobile telephone unit (32) and a personal digital assistant (PDA) unit (31) electronically connected to the mobile telephone unit. The PDA unit (31) is a fully functional personal computer. The PDA unit comprises a memory for application software programs (41), a memory for data (42), a processor (43) for performing operations with the data and the application programs, a modem (33) for passing data between the PDA unit (31) and the mobile telephone unit (32), and a mobile data interface (34) for passing

data between the PDA unit and the mobile telephone unit without utilizing the modem. When the PCT (10) is in the open position, it forms two interior faces which include a PDA display screen (23) on one face and a full alpha-numeric keyboard (24) on the other face. The PCT may be operated as a standard wireless telephone, as a personal computer, or in an integrated mode for FAX, wireless data transfer, or sending and receiving short message service (SMS) messages.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LT	Lithuania	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LV	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MD	Republic of Moldova	TJ	Tajikistan
DK	Denmark	MG	Madagascar	TT	Trinidad and Tobago
EE	Estonia	ML	Mali	UA	Ukraine
ES	Spain	MN	Mongolia	UG	Uganda
FI	Finland	MR	Mauritania	US	United States of America
FR	France			UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

PERSONAL COMMUNICATIONS TERMINAL

BACKGROUND OF THE INVENTION

Technical Field of the Invention

5 This invention relates to mobile stations in a radio telecommunications network and, more particularly, to an integrated personal communications terminal which performs the functions of a mobile telephone while transmitting, receiving, and displaying text or images.

Description of Related Art

10 In modern radio telecommunication systems, subscribers move throughout the coverage area of the system utilizing mobile telephones referred to as mobile stations. Existing mobile telephones have a small display, such as a LED display, for displaying to the subscriber the telephone number being called and the status of the call.

15 Subscriber demand is great for mobile stations with increased communications capabilities. For example, subscribers desire mobile stations capable of transmitting, receiving, and displaying text and images. Heretofore, there has not been a self-contained mobile station capable of operating as a mobile telephone while performing these more advanced functions in a convenient manner. An existing solution has been to use a portable computer such as a laptop or Notepad, such as the Newton Notepad from Apple Computer, which is connected to a mobile telephone so that text and images can be displayed.

20 There are several problems, however, with this existing solution. First, the subscriber must carry around the laptop or Notepad computer in addition to the subscriber's mobile telephone. This is inconvenient at best, and for some subscribers, or in some circumstances, it is not possible. Second, the subscriber must possess the knowledge required to connect the portable computer to the mobile telephone. With the use of mobile

25
30
35

-2-

telephones expanding rapidly within the general population, there are many subscribers who do not possess this knowledge. Third, the subscriber must take time to connect the portable computer to the mobile telephone. Again, this is inconvenient at best, and may result in increased cost to the subscriber since a call is either lengthened by the time it takes the subscriber to connect the computer and the telephone, or two calls must be placed: a first call to alert the subscriber that text or images are to be sent, and a second call to send the text or images.

Although there are no known prior art teachings of a solution to the aforementioned deficiency and shortcoming such as that disclosed herein, a number of prior art references exist that discuss subject matter that bears some relation to matters discussed herein. Such prior art references are U.S. Patent Number 5,348,347 to Shink, a publication titled "Searching for the Perfect PDA", and a publication titled "Is it a phone or a PDA? Here's what Simon says". Each of these references is discussed briefly below.

U.S. Patent Number 5,348,347 to Shink discloses a pocketbook size organizer that can store a portable cellular telephone. The organizer comprises a flexible book that may hold a mobile telephone, a notepad, a pen, a calculator, and a timer. However, Shink does not teach or suggest a personal communications terminal which can perform as a mobile telephone while transmitting, receiving, and displaying text or image data.

The publication titled "Searching for the Perfect PDA" describes three generations of personal digital assistants (PDAs). The first generation comprised palmtop or handheld computers. These palmtops were generally pocket sized with a split case and a hinge on the spine. One side of the palmtop held a display, and the other side held a keyboard. External communication was limited to a serial port for connecting to a desktop computer or

-3-

external modems. The second generation of PDAs was much like the first generation, but added the capability to recognize handwriting entered with a stylus on the display screen. The third generation of PDAs are often called
5 Personal Communications Assistants (PCAs) or Personal Intelligent Communicators (PICs). The most advanced PCA appears to be a device sold by BellSouth Cellular Corporation called Simon.

The publication titled, "Is it a phone or a PDA?
10 Here's what Simon says" is a journal article appearing in the October 31, 1994 issue of InfoWorld magazine at pages 119-120. The article describes the Simon as a device comprising a cellular telephone and a personal digital assistant (PDA). The device may function as a mobile
15 telephone as well as offering communications features such as electronic mail (E-mail) and faxing. The Simon device is not a fully functional personal computer. It is a cellular phone that is also programmed with personal information management (PIM) software applications such
20 as a notepad, address book, calendar, calculator, and the like.

Almost all of one side of the Simon device is a LCD display, but this configuration has several disadvantages. First, since the display covers the entire side of the
25 device, the Simon device must use an on-screen keyboard. When used as a PDA rather than a telephone, the device may display one of two on-screen keyboards or a numeric keypad for use with a calculator application. This creates a second disadvantage, however, since the small size of the
30 on-screen keyboard requires that a stylus be used to make data entries. The on-screen keyboard is not designed for touch typing, but a modest amount of data entry is possible. The on-screen keyboard also creates a third disadvantage because a very limited amount of display area
35 remains for displaying text or graphics information when the keyboard is displayed. While acceptable for straight

-4-

data entry, this solution is not suitable for interactive programs or programming.

5 An additional disadvantage of the Simon device is its exposed display screen which covers virtually all of one side of the device and is therefore extremely vulnerable to impact damage. Great care must be taken when utilizing the Simon device, and this is not always practical when when utilizing a mobile station.

10 It would be a distinct advantage to have a personal communications terminal that overcomes the above-mentioned disadvantages. Such a terminal would have the full capabilities of a personal computer, a keyboard large enough for manual data entry without the use of a stylus, and a display screen with enough usable area for
15 interactive programming. In addition, the display screen would be mounted in a protected location allowing full use of the terminal in a rugged mobile environment.

20 Review of each of the foregoing references reveals no disclosure or suggestion of a system or method such as that described and claimed herein.

SUMMARY OF THE INVENTION

25 In one aspect, the present invention is a personal communications terminal (PCT) in a case having a first half hingedly connected to a second half. The PCT may operate in an open and a closed position and comprises a mobile telephone unit and a personal digital assistant unit electronically connected to the mobile telephone unit. The personal digital assistant unit comprises a
30 first memory device for storing a first set of application software programs, a second memory device for storing a first set of data, and a processor for performing operations with the first set of data utilizing the first set of application software programs. The PCT also
35 includes a power supply for providing electrical power to the mobile telephone unit and the personal digital assistant unit, a modem for passing data between the

-5-

personal digital assistant unit and the mobile telephone unit, and a mobile data interface for passing data between the personal digital assistant unit and the mobile telephone unit without utilizing the modem.

5

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood and its numerous objects and advantages will become more apparent to those skilled in the art by reference to the following drawing, in conjunction with the accompanying specification, in which:

10

FIG. 1 is a front side elevational view of the personal communications terminal (PCT) of the present invention in a closed position;

15

FIG. 2 is a front side elevational view of the PCT of the present invention in an open position and rotated 90 degrees clockwise from the orientation in FIG. 1;

FIG. 3 is a high level block diagram of the components of the PCT in the preferred embodiment of the present invention; and

20

FIG. 4 is a flow chart illustrating the functions performed by the PCT during selection of a mode of operation.

25

DETAILED DESCRIPTION OF EMBODIMENTS

FIG. 1 is a front side elevational view of the personal communications terminal (PCT) 10 of the present invention with its case in a closed position. The front side may include a standard radio telephone display 11 and keypad 12. A telephone power switch 13 is located on an exterior side of the PCT 10 and is utilized to independently power ON or OFF a mobile telephone unit within the PCT 10 when the PCT is in the closed position. When the telephone unit is powered ON, and the PCT is in the closed position, the telephone display 11 displays standard wireless telephone information. A mechanical hinge 14 extends along the spine of the PCT 10 on the left

30

35

-6-

side, enabling the PCT to be selectively swung from a closed to an open position, and vice versa. The hinge allows the PCT to be opened to a full 180 degrees and laid flat in the opened position if desired. The PCT 10 may be utilized as a normal wireless telephone when in the closed position. A rotatable antenna 15 extends from the PCT case. The front side may also include a microphone 16 and a speaker 17.

FIG. 2 is a front side elevational view of the PCT of the present invention in an open position and rotated 90 degrees clockwise from the orientation in FIG. 1. This orientation forms a top half 21 and a bottom half 22 of the PCT 10. The mechanical hinge 14 holds the top half 21 and the bottom half 22 together and covers a data and power cable connecting the two halves. A sensor (not shown) detects whether the phone is in an opened or a closed position.

The top half 21 includes a display screen 23 for use with a personal digital assistant (PDA) unit, and the rotatable antenna 15 for use with the mobile telephone unit. As shown in FIG. 2, the antenna 15 may be rotated in such a way that its orientation is independent of the orientation of the top half 21 in order to optimize transmission and reception qualities. For example, the orientation of the antenna 15 may be maintained approximately vertical regardless of the orientation of the top half 21 in order to optimize transmission and reception of wireless telephone signals.

The bottom half 22 includes a full alpha-numeric personal computer keyboard 24 for use with the PDA. The keyboard 24 includes a PDA power switch 25 and an interior telephone power switch 26 which are utilized to power on/off the PDA unit and the telephone unit, respectively, when the PCT 10 is being operated in the open position. A PDA power-on light indicator 27 and a telephone power-on light indicator 28 are mounted adjacent to the PDA and telephone power switches 25 and 26, and indicate whether

-7-

the PDA unit and/or the telephone unit are energized. The indicators can only be seen when the PCT is in the open position. The PCT is OFF when in the closed position unless the telephone unit is individually energized utilizing the external telephone power switch 13 (FIG. 1). The keyboard 24 may also include an optional trackball 29 to move a cursor around the PDA display screen 23.

If the telephone unit is powered ON by using the external telephone power switch 13, the telephone power-indicator light 28 comes ON when the PCT is opened. Power-indicators 27 and 28 are OFF when the PCT is closed.

FIG. 3 is a high level block diagram of the components of the PCT in the preferred embodiment of the present invention. Functionally, the PCT 10 is divided into a personal digital assistant (PDA) functional unit 31, a telephone functional unit 32, a modem 33, a mobile data-interface (MDI) unit 34, and a PDA Open sensor 35. The MDI unit 34 transfers data directly between the PDA unit 31 and the telephone unit 32 without the use of the modem 33. The MDI may be implemented as a RAM memory device with common access by both the PDA unit 31 and the telephone unit 32. The RAM memory device may be separate from the PDA RAM 42 or may be a reserved portion of the PDA RAM 42. Data transferred through the MDI 34 may include, for example, telephone numbers entered on the PDA keyboard and the state of the PDA Open sensor 35.

A connecting circuit (not shown) electronically connects the PDA unit 31, the telephone unit 32, the modem 33, the MDI unit 34, and the PDA Open sensor 35. Two power supply units (batteries) 36 and 37 supply electrical power to the PCT. The batteries are located in the bottom half 22 of the PCT which includes the PDA keyboard 24. This configuration provides a low center of gravity and stability to the PCT 10. A high power supply 36 provides high power to the wireless telephone unit 32 and the PDA unit 31. A low power supply 37 provides a back-up power source for the PDA unit 31 when the high

-8-

power supply 36 is detached from the unit for charging or when its energy level is low. Power to the PDA unit 31 is turned OFF when the PCT 10 is in the closed position. Power may still be supplied to the telephone unit 32 in the closed position if the telephone unit is in use.

Other components of the PDA unit 31 include a read only memory (ROM) 41 for storing application programs and providing limited operations of the PDA unit when operating off the low power supply 37. The PDA unit also includes a random access memory (RAM) 42 for storing data, the PDA display screen 23, the PDA keyboard 24, a PDA central processing unit (CPU) 43 which may be a microprocessor for timing and control of the PDA, an accumulator/register 44 contained within the PDA CPU 43, various input/output (I/O) ports 45, and a hard drive memory device 46. The I/O ports 45 send and receive data from, for example, the mobile data interface 34, the modem 33, the PDA Open sensor 35, and external sources of application software programs 47 and data which may be loaded onto the hard drive memory 46. The hard drive memory device 46 stores application software programs and data, and provides the PDA unit with full personal computer capabilities. The hard drive is powered from the high power source 36.

When electrical power from the power supplies exceeds the minimum power level required for operation of the hard drive, the PDA unit 31 may utilize the hard drive to access application software programs stored there. This capability, combined with the PDA's full alpha-numeric keyboard 24 and PDA screen 23, make the PDA a fully functional personal notepad computer. Telephone (PHONE) and facsimile (FAX) functions are also performed and may be indicated with icons shown on the PDA screen 23 or as selections on a pull-down menu. When electrical power from the power supplies is less than the minimum power level required for operation of the hard drive, the PDA

- 9 -

unit 31 may utilize the ROM 41 to access the application software programs stored there.

5 The telephone unit 32 includes a mobile station CPU 51, the mobile telephone display screen 11, the mobile telephone keypad 12, the microphone 16, the speaker 17, and transmit and receive subsystems. The transmit subsystem includes a transmit digital signal processor (DSP) 52, a transmit application specific integrated circuit (ASIC) 53, and a radio transmitter 54. The
10 receive subsystem includes a radio receiver 55, a receive ASIC 56, and a receive DSP 57. The telephone unit 32 is capable of operating on either an analog control channel or a digital control channel. The telephone unit 32 is also multi-hyperband capable, and may operate on the 800-
15 MHz wireless telephone frequency hyperband as well as other hyperbands such as the 1900-MHz personal communication system (PCS) frequency hyperband.

The following functions are performed by the PDA unit 31:

- 20
- Calculator;
 - Agenda;
 - Clock;
 - Notepad; and
 - Editors (Text, Graphics, Image).
- 25

Making a Call

If the PCT 10 is in the closed position, a telephone call is made in the same manner as calls placed on an ordinary wireless telephone. If the PCT is in the open
30 position, the user may select the PHONE application on the PDA display 23. A LIST function is then displayed, and if selected, presents a list of telephone numbers from which to choose. The user may select a phone number from the list by highlighting the number and pressing the
35 <ENTER> key on the PDA keyboard 23, or by double-clicking the number with the trackball 29. If the telephone unit 32 is not already turned on, it is then turned on, and the

-10-

selected number is automatically dialed by the PDA unit 31, by transmitting the number through the mobile data interface 34 to the telephone unit. If the telephone number to be called is not on the list of telephone numbers presented, the user may enter the telephone number utilizing the PDA keyboard 24. By then pressing the <ENTER> key, the entered number is automatically dialed by the PDA unit, by transmitting the number through the mobile data interface to the telephone unit. The user may then close the two halves of the PCT 10 and use it as an ordinary wireless telephone.

Sending a Facsimile (FAX)

The PCT 10 must be in the open position to send a Fax. The user may utilize a Text Editor to edit the message, and then may select the FAX application on the PDA display 23. A list of telephone numbers is then displayed, and the user may select a phone number from the list by highlighting the number and pressing the <ENTER> key on the PDA keyboard 24, or by double-clicking the number with the trackball 29. If the telephone unit 32 is not already turned on, it is then turned on, and the selected number is automatically dialed by the PDA unit 31, by transmitting the number through the mobile data interface 34 to the telephone unit. Once the telephone connection is made to the called number, the Fax message is sent through the modem 33 to the telephone unit.

Using the PCT as a Wireless Data Terminal

The PCT 10 may also be utilized as a Wireless Data Terminal (WDT) to send and receive messages such as Short Message Service (SMS) messages. The PCT must be in the open position to use this function. Upon receiving a SMS message, the PCT displays the text of the SMS message on the PDA display screen 23 and provides a SMS warning tone. Upon hearing the SMS warning tone, the user may open the PCT and read the message on the PDA display.

-11-

To send a SMS message utilizing the PCT 10, the user may utilize the Text Editor to edit the message, and then selects the SMS application on the PDA display screen 23. A list of telephone numbers is then displayed, and the user may select a phone number from the list by highlighting the number and pressing the <ENTER> key on the PDA keyboard 24, or by double-clicking the number with the trackball 29. If the telephone unit 32 is not already turned on, it is then turned on, and the SMS message is automatically sent through the mobile data interface 34 to the telephone unit.

To use the PCT 10 as a wireless data terminal, the user selects the Data Terminal (DT) application. A list of remote computer telephone numbers is then displayed on the PDA display screen 23. The user enters or selects a desired telephone number from the list. Once the telephone number of a remote computer is selected, it is automatically dialed by the PDA 31, and the data communication is established through the modem 33 to the telephone unit 32. The user may then start a dialogue with the remote computer, utilizing the PCT as a Data Terminal.

FIG. 4 is a flow chart illustrating the functions performed by the PCT 10 during selection of a mode of operation. The process begins at step 61 where the PCT determines from a reading from the PDA-Open sensor 35 whether the PCT is in the open position or the closed position. If it is determined that the PCT is in the closed position, the process moves to step 62 where it is determined whether or not power is ON to the telephone unit 32. If power to the telephone unit is ON, the process moves to step 63 where normal wireless telephone functions are enabled. If, however, it is determined at step 62 that power is not ON to the telephone unit, then the process moves to step 64 where the process stops and no functions are enabled.

-12-

Returning to step 61, if the PDA-Open sensor 35 reported that the PCT was in the open position, then the process moves to step 65 where it is determined whether or not power is ON to the PDA unit 31. If power is not
5 ON to the PDA unit 31, then the process moves to step 66 where it is determined whether or not power is ON to the telephone unit 32. If it is determined at step 66 that power is not ON to the telephone unit, then the process returns to step 64 where the process stops and no
10 functions are enabled. If, however, it is determined at step 66 that power is ON to the telephone unit, then the process moves to step 67 where normal wireless telephone functions are enabled, and the PDA keyboard 24 is enabled for entering telephone numbers.

15 Returning to step 65, if the power is ON to the PDA unit 31, then the process moves to step 68 where it is determined whether or not power is ON to the telephone unit 32. If it is determined at step 68 that power is ON to the telephone unit, then the process moves to step 69
20 where PDA functions, normal wireless telephone functions, and FAX functions are enabled. If, however, it is determined at step 68 that power is not ON to the telephone unit, then the process moves to step 71 where PDA functions only are enabled.

25 The process then moves to step 72 where it is determined whether the user has requested the PDA unit 31 to execute a phone or a FAX function by entering a telephone number or a FAX number on the PDA. If not, the process moves to step 73 and executes other applications.
30 If the user has requested the PDA to execute a phone or a FAX function, the process moves to step 74 where the PDA unit 31 turns on the telephone unit 32. At step 75, the process then passes the telephone or Fax number to the telephone unit 32 through the mobile data interface 34.

35 It is thus believed that the operation and construction of the present invention will be apparent from the foregoing description. While the method,

-13-

apparatus and system shown and described has been characterized as being preferred, it will be readily apparent that various changes and modifications could be made therein without departing from the spirit and scope
5 of the invention as defined in the following claims.

-14-

WHAT IS CLAIMED IS:

1. A personal communications terminal in a case having a first half hingedly connected to a second half, said personal communications terminal operating in an open and a closed position, said personal communications terminal comprising:
- a mobile telephone unit;
 - a personal digital assistant unit electronically connected to said mobile telephone unit, said personal digital assistant unit comprising:
 - a first memory device for storing a first set of application software programs;
 - a second memory device for storing a first set of data; and
 - a processor for performing operations with said first set of data utilizing said first set of application software programs;
 - a power supply for providing electrical power to said mobile telephone unit and said personal digital assistant unit;
 - a modem for passing data between said personal digital assistant unit and said mobile telephone unit; and
 - a mobile data interface for passing data between said personal digital assistant unit and said mobile telephone unit without utilizing said modem.
2. The personal communications terminal of claim 1 wherein said first memory device is a read only memory (ROM).
3. The personal communications terminal of claim 2 wherein said second memory device is a random access memory (RAM).
4. The personal communications terminal of claim 1 wherein said personal digital assistant unit includes

-15-

a third memory device that stores a second set of data and a second set of application software programs.

5 5. The personal communications terminal of claim
4 4 wherein said third memory device is a hard drive
 memory.

10 6. The personal communications terminal of claim
5 5 further comprising means for accessing said second set
 of data and said second set of application software
 programs stored in said hard drive memory when said
 electrical power from said power supply exceeds a
 predetermined threshold.

15 7. The personal communications terminal of claim
6 6 further comprising means for accessing said first set
 of application software programs stored in said first
 memory device and said first set of data stored in said
 second memory device when said electrical power from said
20 power supply is less than said predetermined threshold.

25 8. The personal communications terminal of claim
7 7 further comprising an input/output (I/O) port for
 inputting to said hard drive memory and outputting from
 said hard drive memory, said second set of application
 software programs and said second set of data .

30 9. The personal communications terminal of claim
8 8 wherein said second set of application software
 programs includes all personal computer software
 application programs.

35 10. The personal communications terminal of claim
9 9 wherein said mobile telephone unit includes:
 means for operating on an analog control channel; and
 means for operating on a digital control channel.

-16-

11. The personal communications terminal of claim 9 wherein said mobile telephone unit includes means for transmitting and receiving on a plurality of frequency hyperbands.

5

12. The personal communications terminal of claim 11 wherein said means for transmitting and receiving on a plurality of frequency hyperbands includes:

means for transmitting and receiving on a 800-MHz frequency hyperband; and

10

means for transmitting and receiving on a 1900-MHz frequency hyperband.

13. The personal communications terminal of claim 12 wherein said mobile telephone unit includes:

15

a telephone display screen;

a keypad for entering instructions and data that are displayed on said telephone display screen; and

a telephone power switch that energizes said mobile telephone unit independently from said personal digital assistant unit.

20

14. The personal communications terminal of claim 13 wherein said telephone display screen is located on an exterior side of said personal communications terminal.

25

15. The personal communications terminal of claim 14 wherein said keypad is located on said exterior side of said personal communications terminal adjacent said telephone display screen.

30

16. The personal communications terminal of claim 15 wherein said mobile data interface passes telephone numbers from said personal digital assistant unit to said mobile telephone unit without utilizing said modem.

35

-17-

17. The personal communications terminal of claim 16 wherein said personal communications terminal includes:

5 means for determining whether a user of said personal digital assistant unit has requested that the personal communications terminal perform a telephone or a facsimile function when power to said mobile telephone unit is off; and

10 means for turning on said mobile telephone unit upon determining that said user has requested that the personal communications terminal perform a telephone or a facsimile function.

15 18. The personal communications terminal of claim 17 wherein said means for turning on said mobile telephone unit includes means for passing an instruction from said personal digital assistant unit to said mobile telephone unit through said mobile data interface unit, said instruction turning on said mobile telephone unit.

20 19. The personal communications terminal of claim 18 further comprising a sensor that senses whether said personal communications terminal is in the open or the closed position.

25 20. The personal communications terminal of claim 19 wherein a first interior face and a second interior face are formed when said PCT is in the open position, said first interior face including a display screen for said personal digital assistant unit.


30 21. The personal communications terminal of claim 20 wherein said second interior face includes an alphanumeric keyboard for inputting instructions and data to said personal digital assistant unit.

-18-

22. The personal communications terminal of claim
21 wherein said personal digital assistant unit includes
a personal digital assistant power switch that energizes
5 said personal digital assistant unit independently from
said mobile telephone unit.


1 / 4

FIG. 1



2 / 4

FIG. 2



3 / 4

FIG. 3





FIG. 4



INTERNATIONAL SEARCH REPORT

International Application No
PCT/SE 96/00992

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04M1/72

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04M H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US,A,4 972 457 (O'SULLIVAN) 20 November 1990	1-5
A	see column 2, line 45 - column 3, line 11 see column 4, line 55 - column 9, line 14; figures 1-4 see column 11, line 13 - column 12, line 2; figures 1-4 see column 13, line 32 - column 18, line 55; figures 1-10 ---	16-18
Y	WO,A,90 03076 (INTELLIGENCE TECHNOLOGY CORP) 22 March 1990	1-5
A	see page 5, line 9 - page 17, line 15; figures 1-9 ---	6-9,13, 22
Y	EP,A,0 651 544 (IBM) 3 May 1995	1
A	see column 3, line 29 - column 6, line 6; figures 1-3 ---	2-5
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

21 November 1996

Date of mailing of the international search report

11.12.96

Name and mailing address of the ISA:

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Delangue, P

INTERNATIONAL SEARCH REPORT

Intern: J Application No
PCT/SE 96/00992

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y A	EP,A,0 472 361 (NOKIA) 26 February 1992 see column 2, line 17 - column 4, line 1; figures 1-3 ---	1 2-5
A	WO,A,95 14275 (ETE INC) 26 May 1995 see page 4, line 10 - page 10, line 16; figures 1-4 see page 30, line 27 - page 48, line 34; figures 10-14 ---	1-9, 16-18
A	US,A,5 335 276 (THOMPSON ET AL) 2 August 1994 see column 6, line 55 - column 11, line 37; figures 1-8 see column 13, line 6 - line 21; figure 8 see column 15, line 28 - column 17, line 24; figure 10 ---	1-9,11, 12,19-21
A	WO,A,95 14359 (QUALCOMM INC) 26 May 1995 see page 2, line 34 - page 4, line 36; figures 1-3 ---	1
A	EP,A,0 415 502 (PHILIPS ELECTRONICS UK LTD) 6 March 1991 see page 4, line 3 - page 5, line 18; figures 1-4 ---	11,12
A	US,A,5 420 911 (DAHLIN ET AL) 30 May 1995 see abstract -----	10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/SE 96/00992

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-4972457	20-11-90	NONE	
WO-A-9003076	22-03-90	US-A- 4991197 AU-A- 4310289 EP-A- 0387338	05-02-91 02-04-90 19-09-90
EP-A-0651544	03-05-95	JP-A- 7193866	28-07-95
EP-A-0472361	26-02-92	DE-D- 69118619 DE-T- 69118619 ES-T- 2085431 US-A- 5189632	15-05-96 05-09-96 01-06-96 23-02-93
WO-A-9514275	26-05-95	US-A- 5497339 AU-A- 1176895	05-03-96 06-06-95
US-A-5335276	02-08-94	NONE	
WO-A-9514359	26-05-95	AU-A- 1175595	06-06-95
EP-A-0415502	06-03-91	GB-A- 2236454 AU-B- 649959 AU-A- 6195290 CA-A- 2024216 JP-A- 3093328 US-A- 5212684	03-04-91 09-06-94 07-03-91 02-03-91 18-04-91 18-05-93
US-A-5420911	30-05-95	CA-A- 2077095 SE-A- 9202453	01-03-93 01-03-93